



UR90G-SUB ZERO

Caviar Cooler

Product Features

- Internal vertical LED light
- Black interior and exterior
- Great product presentation
- Heated glass door
- Adjustable shelves
- Adjustable feet

Sub zero table top freezer ideal as caviar cooler

UR90G-SUB ZERO is a tabletop freezer optimized for cooling caviar and other products you may want to keep at sub-zero temperatures.

The sub-zero model has an electronic thermostat and thermometer, which makes sure that the sensitive caviar is not exposed to wrong temperatures.

Ideally caviar should be stored at -6 to 0 degrees Celsius. An ordinary cooler is too warm, and an ordinary freezer is too cold. Storage under wrong temperatures will ruin the quality of the caviar.

A ventilated cooling system makes sure the temperature is even and stable on all shelves.

The thermostat is placed at the back of the unit, so that the temperature is not changed by accident.

Besides functionality and quality, we have also focused on the visual impression. The unit has a sleek design with internal LED lighting in a cold color tone. It has a black interior as well as exterior. It has heated double glass in the door to prevent condensation. The content is presented in the best possible way.

Measures and Content

Gross / Net Weight	kg	39.5 / 35.5
Net Volume	l	81
Gross Volume	l	92
Gross / Net Volume	l	92 / 81
Temperature Range	°C	-8 to +6
Climate Class		4

Design and Material

Exterior Finish		Black
Interior Finish		Black
No. of Doors		1
Door No & Type		1 heated hinged glass door
Door Reversible		No
No. of Shelves	pcs	3
Shelves No & Type		3 wire shelves black
Shelf Color		Black
Shelf Dimensions		420 x 300 mm
Tempered glass		Yes
Feet / Legs		4 adjustable feet
Lock		Yes
Interior Light		LED cold white vertically

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Compressor Type		EMT2125U
Refrigerant		R600a
Refrigerant Charge	g	40
Thermometer		Yes

Power and Consumption

Energy Class		E
Energy Consumption	kWh/24h	1.51
Annual Energy Cons.	kWh/year	551
EEl	%	58
Input Power	W	280
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	42

Dimensions

External Dimension (WxDxH)	mm	515 x 542 x 750
Internal Dimension (WxDxH)	mm	439 x 299 x 632
Packed Dimension (WxDxH)	mm	570 x 585 x 805
40ft Container Load	pcs	160



Lock



LED light inside door

