



CK7210X1SP

Counter Cooler GN1/1

Product Features

- Stainless steel
- Controller with Bluetooth and NFC connectivity
- HACCP compliant data export
- Self-closing doors
- Ventilated cooling
- Automatic defrost
- Adjustable legs
- 1/2 and 1/3 drawers as option

Stainless steel counter cooler with GN1/1 shelves

The CK7210X1SP is an energy-efficient counter cooler for professional settings. It has a 48% lower energy consumption compared to the previous CK7210 model.

The CK counter cooler is made for professional kitchens, and it offers an ideal solution for keeping ingredients chilled and within easy reach during service. It is made from durable SS304 stainless steel and features automatic defrost and GN1/1 dimensioned shelves for easy cleaning and smooth workflows. The legs are adjustable so it is possible to adapt the height of the table to your needs.

Its ventilated cooling system keeps contents at a consistent temperature, and the electronic controller makes it easy to adjust the temperature to fit your ingredients. The controller has Bluetooth and NFC-connectivity. This means that you via an app can control the lighting, keep an eye of the temperature of the cabinet, and even export data for easy reporting. The CK counter cooler makes an excellent addition to any professional kitchen.

Measures and Content

Gross / Net Weight	kg	122 / 112
Net Volume	l	190
Gross Volume	l	238
Gross / Net Volume	l	238 / 190
Temperature Range	°C	-2 to +8
Climate Class		5

Design and Material

Exterior Finish	SS304
Interior Finish	SS304
No. of Doors	2
Door No & Type	2 hinged self-closing doors
Door Reversible	No
No. of Shelves	pcs2
Shelves No & Type	2 wire shelves grey
Shelf Color	Grey
Feet / Legs	4 adjustable legs
Lock	No

Cooling and Functions

Type of Controller	Electronic
Type of Cooling	Ventilated
Type of Defrost	Automatic
Refrigerant	R600a
Refrigerant Charge	g95
Thermometer	Yes

Power and Consumption

Energy Class		A
Energy Consumption	kWh/24h	1.03
Annual Energy Cons.	kWh/year	376
EEl	%	16.5
Input Power	W	300
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	38

Dimensions

External Dimension (WxDxH)	mm	1360 x 700 x 960
Internal Dimension (WxDxH)	mm	799 x 580 x 564
Packed Dimension (WxDxH)	mm	1390 x 730 x 1010
40ft Container Load	pcs	48



GN1/1 shelves



Drawers available as separate kit