

GLASS & DISHWASHERS WITH DOUBLE SKIN DOOR

Range: GS

The glass and dishwashers of the GS series are ideal for bars, pubs, restaurants and hotels.

These undercounter machines, with a redesigned control panel, feature a wide loading capacity granting the highest performance at a reasonable price. According to the user's needs the machine can be customized thanks to many optional features such as water softener, detergent dispenser and drain pump.



FEATURES

- Electronic control panel
- Solid structure in AISI 304 S/S
- Sound and heat proof double skin door
- Door with anti-shock system
- Deep-drawn and sloped tank for a perfect total drain
- Non-drip roof to safeguard the hygiene of the freshly washed dishes
- Light rinse arms granting the best efficiency also in the event of weak pressure in the water mains
- Easy to remove nozzles to help with daily cleaning operations
- Overflow and drain pipes integrated system for a triple protection of the wash pump
- 4 preset wash cycles
- Self-cleaning cycle
- Soft Start wash pump that offers additional protection for the most delicate objects
- Non-return valve to prevent the water backflow
- Thermostop system: the rinse starts only when the water in boiler reaches 85 °C
- Rinse aid dispenser

OPTIONS

- Special voltages
- Drain pump
- Built-in peristaltic detergent dispenser
- Peristaltic rinse aid dispenser
- Final rinse with cold water
- Round basket
- Built-in water softener with automatic regeneration
- Upper wash arms (plates with a maximum diameter of 295 mm)

Option compatibility to be confirmed by the manufacturer after verification

CAPACITY




305 H 400x400

RACK EQUIPMENT

- 2 X C121
- 1 X 10728
- 1 X 15060



GLASS & DISHWASHERS WITH DOUBLE SKIN DOOR



TECHNICAL FEATURES

EXTERNAL DIMENSIONS

Width	mm	450
Depth	mm	535
Height (screwed foot)	mm	700
Weight (standard version)	kg	37

TECHNICAL DATA

Basket dimensions	mm	400x400
Glasses maximum useful height	mm	305
Maximum level of water discharge	mm	65
Water inlet temperature	°C	55
Maximum inlet water hardness	°f	8
Inlet water pressure	kPa	200 - 400
Tank capacity	l	14.5
Tank heating element	kW	1.25
Boiler capacity	l	3.4
Boiler heating element	kW	2.8
Wash pump power	kW	0.4
Wash pump flow rate	l/min	185
Sound pressure level	dB(A)	< 70

POWER SUPPLY DATA

Supply voltage		220-240 V 50 Hz
Total installed power	kW	3.2

GLASS & DISHWASHERS WITH DOUBLE SKIN DOOR

CYCLES					
Cycle number		1	2	3	4
Cycle length	s	60	90	120	180
Cycle productivity (racks/h) - 55°C inlet water		60	40	30	20
Cycle productivity (racks/h) - 10°C inlet water		16	16	16	16
Cycle water consumption	l	1.8	1.8	1.8	1.8
Rinsing temperature setting	°C	85	85	85	85
Washing temperature setting	°C	55	55	55	55

Standard Thermostop. In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.